

As defined in its Terms of Reference, the European UAS Standards Coordination Group (EUSCG) is a joint coordination and advisory group established to coordinate the standardisation activities related to Unmanned Aircraft Systems. The Rolling Development Plan (RDP) is periodically updated to reflect the current situation. It may therefore not be exhaustive in some areas. Its contents should be used for information purposes only and should not be used as any regulatory reference.

Standards related to Cyber Security are covered by the European Cyber security for aviation Standards Coordination Group (ECSCG). The ECSCG RDP is available at www.ecscg.eu

Standards related to ATM are covered by the European ATM Standards Coordination Group (EASCG). The EASCG RDP is available at www.eascg.eu"

Information about EUSCG SDO documents

ASTM	Test method - a definitive procedure that produces a test result.
	Guide - information or series of options that does not recommend a specific course of action.
	Practice - a definitive set of instructions for performing one or more specific operations that does not produce a test result.
	Classification - a systematic arrangement or division of materials, products, systems, or services into groups based on similar characteristics such as origin, composition, properties, or use.
	Terminology - a document comprising definitions of terms; explanations of symbols, abbreviations, or acronyms.
EUROCAE	Minimum Aviation Systems Performance Standards (MASPS) - describes and specifies the operational and/or functional requirements of a complete end-to-end system, which may include airborne, on-ground and space segments. It should provide a high-level architecture describing the individual components, and should allocate between those components the performance, safety and interoperability requirements.
	Operational Services and Environment Definition (OSED) - a document dedicated to the operational concept description: it provides the definition of the considered services and of the environment, in which they have to be provided. It is usually published as an annex to the SPR.
	Safety and Performance Requirements Standard (SPR) - a standalone document dedicated to operational safety and performance issues: it provides an allocation of the requirements between the segments for the different approval types.
	Interoperability requirements standard (INTEROP) - a standalone document dedicated to interoperability issues between the different segments: for each of them, it identifies the technical interface and related functional requirements
	Process Standard - specifies generic methods, which are not specific to individual components, e.g. software or hardware development, environmental testing
	Minimum Operational Performance Standard (MOPS) - specifies the performance of a component (piece of equipment, protocols, exchange formats, ...), which is the minimum necessary performance to satisfy a regulatory requirement. In particular, it specifies the tests to be made to ensure that the specified performance is achieved.
	Technical Standard - specifies performance of a component, which reflects the best industrial practice.
	Guidance Document - supplements the information contained in the types of documents described above. Usually illustrative information to another EUROCAE document.
	Internal Report - represents the opinion of a WG on a certain technical topic. It is identified with a WG reference number and date only.

EUROCONTROL	Specifications - Define technical and/or operational procedures that advance ATM
	Guidelines - Provide more general implementation support to stakeholders.
	NOTE: Standards are developed and maintained as both harmonising standards and as means of compliance. Standards are used as reference material by ICAO and EASA, and continue to provide the basis of Community Specifications for the extant EU SES regulations in accordance with regulation EC 552/2004 (Interoperability Regulation).
ISO	International Standard - provides rules, guidelines or characteristics for activities or for their results, aimed at achieving the optimum degree of order in a given context. It can take many forms. Apart from product standards, other examples include : test methods, codes of practice, guideline standards and management systems standards.
	Technical Specification - addresses work still under technical development, or where it is believed that there will be a future, but not immediate, possibility of agreement on an International Standard. A Technical Specification is published for immediate use, but it also provides a means to obtain feedback. The aim is that it will eventually be transformed and republished as an International Standard.
	Technical Report - contains information of a different kind from that of the previous two publications. It may include data obtained from a survey, for example, or from an informative report, or information of the perceived “ state of the art ”.
	Publicly Available Specification - is published to respond to an urgent market need, representing either the consensus of the experts within a working group, or a consensus in an organization external to ISO. As with Technical Specifications, Publicly Available Specifications are published for immediate use and also serve as a means to obtain feedback for an eventual transformation into an International Standard. Publicly Available Specifications have a maximum life of six years, after which they can be transformed into an International Standard or withdrawn.
	International Workshop Agreement - is a document developed outside the normal ISO committee system to enable market players to negotiate in an “ open workshop ” environment. International Workshop Agreements are typically administratively supported by a member body. The published agreement includes an indication of the participating organizations involved in its development. An International Workshop Agreement has a maximum lifespan of six years, after which it can be either transformed into another ISO deliverable or is automatically withdrawn.
	Guides - help readers understand more about the main areas where standards add value. Some Guides talk about how, and why, ISO standards can make it work better, safer, and more efficiently.
SAE	Standards - these Technical Reports are a documentation of broadly accepted engineering practices or specifications for a material, product, process, procedure or test method.
	Recommended Practices - these Technical Reports are documentations of practice, procedures and technology that are intended as guides to standard engineering practice. Their content may be of a more general nature, or they may propound data that have not yet gained broad acceptance.
	Information Reports - these Technical Reports are compilations of engineering reference data or educational material useful to the technical community.
	Aerospace Material Specifications - these Technical Reports identify material and process specifications conforming to sound, established engineering and metallurgical practices in aerospace sciences and practices.

Change A=added D=deleted M=modified	Domains	Regulatory activity	Content of the Regulation	Regulatory organisation	Target date for regulatory material publication	EASA UAS categories	Status	Standardisation activity	Short description of the deliverable	SDO	Target date for publication	Type of document (standard, supporting material etc.)	Status	Comments
1 General														
	Definition and classification							AS6969	This data dictionary provides a mathematically coherent set of definitions for quantity types used in data models for unmanned systems. In this data dictionary, a quantity is defined as a property of a phenomenon, substance, or body whose value has magnitude.	SAE AS-4UCS Unmanned Systems (UAS) Control Segment Architecture	jun-18	standard	ongoing	
	Definition and classification							ARPE128 Unmanned Systems Terminology Based on the ALFUS Framework	This SAE Aerospace Recommended Practice (ARP) describes terminology specific to unmanned systems (UMS) and definitions for those terms. It focuses only on terms used exclusively for the development, testing, and other activities regarding UMS. Terms that are used in the community but can be understood with common dictionary definitions are not included in this document. Further efforts to expand the scope of the terminology are being planned.	SAE AS-UJUS Joint Architecture for Unmanned Systems Committee		recommended practice	published	
	Definition and classification							AS### UAS Propulsion System Terminology		SAE E-39 Unmanned Aircraft Propulsion Committee	mai-19	standard	planned	
	Definition and classification							F3341/F3341M-20 Standard Terminology for Unmanned Aircraft Systems	This terminology covers definitions of terms and concepts related to unmanned aircraft systems (UAS). It is intended to encourage the consistent use of terminology throughout all ASTM International UAS standards. Audience: Committee F38, ASTM International, the UAS industry, and the global community. 1.2 This terminology contains a listing of terms, abbreviations, acronyms, and symbols related to aircraft covered by Committees F38 standards. Cross-referenced terms (for example, see or compare) are for information only and provide support or clarification.	ASTM F38 Unmanned Aircraft Systems	Mar-18	standard	published	
	Definition and classification							ISO 21895 - Requirements for the categorization and classification of civil UAS	Requirements for the categorization and classification of civil UAS. The standard applies to their industrial regulation, development and production, delivery and usage.	ISO TC20/SC16/WG1		standard	published	At DIS stage and publicly available first week of April 2019.
	Definition and classification							ISO 21384-1 - General requirements for UAS for civil and commercial applications. UAS terminology and classification	Provides the foundation and common terms, definitions and references relevant to the whole Standard, the purpose of which is to provide a safety quality standard for the safe operation of all UAS through the provision of synergistic standards for manufacturing and operations.	ISO TC20/SC16/WG1	May-21	standard	ongoing	At DIS stage and publicly available first week of April 2019.
								ISO 21384-4 - Unmanned aircraft systems – Part 4: Terms and definitions	Provides terms and definitions to support ISO/TC 20/SC 16 standards	ISO TC20/SC16/WG1		standard	published	
	Definition and classification							ASTM WK62744 General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS)	This standard defines the requirements for General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS). The standard addresses the requirements and/or best practices for documentation and organization of a professional operator (i.e., for compensation and hire). The intent is for this standard to support professional entities that will receive operator certification by a CAA, and provide standards of practice for self- or third-party audit of operators of UAS. Not all CAAs have operator certificates. This would provide a standard for operators and identify gaps that are not currently addressed as it relates to: (1) Individuals, who are currently remote pilots (i.e. FAA under Part 107) in jurisdictions that do not separately certify Operators, who want to voluntarily comply with a higher standard; and (2) Operators, who are seeking certification from a CAA for Light Unmanned Aircraft Systems, who want to voluntarily comply with an industry standard (3) Public agencies interested in developing unmanned aircraft systems programs.	ASTM F38 Unmanned Aircraft Systems	mars-19	standard	onging	
	Manuals							ASTM F3366-19 Standard Specification for General maintenance Manual (GMM) for small Unmanned Aircraft Systems (sUAS)	This specification provides the minimum requirements for a General Maintenance Manual (GMM) for an unmanned aircraft system (UAS) designed, manufactured, and operated in the small UAS category as defined by a Civil Aviation Authority (CAA).	ASTM F38 Unmanned Aircraft Systems		standard	published	

Operator organisations	EASA Decision	OSO #08 - Operational procedures are defined, validated and adhered to (to address technical issues with the UAS); Criteria 1, 2,3	EASA	oct-19	Specific	published													
Operator organisations	EASA Decision	OSO #11 - Procedures are in-place to handle the deterioration of external systems supporting UAS operation; Criteria 1, 2,3	EASA	oct-19	Specific	published													
Operator organisations	EASA Decision	OSO #14 - Operational procedures are defined, validated and adhered to (to address Human Errors); Criteria 1, 2,3	EASA	oct-19	Specific	published													
Operator organisations	EASA Decision	OSO #21 - Operational procedures are defined, validated and adhered to (to address Adverse Operating Conditions); Criteria 1, 2,3	EASA	oct-19	Specific	published													
Operator organisations	EASA Decision	OSO#19 Safe recovery from Human Error (<u>Criterion #1 Procedures and checklists</u>)	EASA	oct-19	Specific	published													
Operator organisations	EASA Decision	OSO#16 Multi crew coordination. (<u>Criterion #1 Procedures</u>)	EASA	oct-19	Specific	published													
Operator organisations	EASA Decision	OSO#23 Environmental conditions for safe operations defined, measurable and adhered to (Criterion #1 Procedures)	EASA	oct-19	Specific	published													
Operator organisations	EASA Decision	MF1 An Emergency Response Plan (ERP) is in place, operator validated and effective (Criterion #1 Operational)	EASA	oct-19	Specific	published													
							ISO/WD 24356	General requirements for tethered unmanned aircraft system	ISO TC20 SC16	mai-21	standard	ongoing							
							ASTM	ASTM 2483-18: Standard Practice for Maintenance and the Development of Maintenance Manuals for Light Sport Aircraft	ASTM		standard	published	Standard added to RDP as it was recommended by AW-Drones						
							ATA	ATA MSG-3 - Operator/Manufacturer Scheduled Maintenance Development	ATA		standard	published	Standard added to RDP as it was recommended by AW-Drones						
							JAP	JAP(D)100C-22 - Guide to Developing and Sustaining Preventive Maintenance Programmes	Ministry of Defence and Military Aviation Authority (GOV UK)		standard	published	Standard added to RDP as it was recommended by AW-Drones						
							EN 16803-1:2016 - Space - Use of GNSS-based positioning for road Intelligent Transport Systems- Part 1- Definitions and system engineering procedures for the establishment and assessment of performance	EN 16803-1 addresses the final stage of the performance management approach, i.e. the assessment of the whole Road ITS system performance equipped with a given GBPT, using the Semiotic analysis method. EN 16803-1 addresses the assessment of GBPT performance, since it identifies and defines the positioning performance features and metrics to be used in the definition of the GBPT performance requirements. This EN gives definitions of the various items to be considered when specifying an Operational scenario and provides a method to compare finely two environments with respect to their effects on GNSS positioning performance. This EN gives definition of the most important terms used all along the document and describes the architecture of a Road ITS system based on GNSS as it is intended in this standard. This EN does not address: - the performance metrics to be used to define the Road ITS system performance requirements, highly depending on the use case and the will of the owner of the system; - the performance requirements of the various kinds of Road ITS systems; - the tests that are necessary to assess GBPT performance (field tests for this purpose will be addressed by EN 16803-2 and EN 16803-3).	CENELEC		standard	completed	Standard added to RDP as it was recommended by AW-Drones						

										EN 16803-1 addresses the final stage of the performance management approach, i.e. the assessment of the whole Road ITS system performance equipped with a given GBPT, using the Sensitivity analysis method. EN 16803-1 addresses the assessment of GBPT performance, since it identifies and defines the positioning performance features and metrics to be used in the definition of the GBPT performance requirements. This EN gives definitions of the various items to be considered when specifying an Operational scenario and provides a method to compare finely two environments with respect to their effects on GNSS positioning performance. This EN gives definition of the most important terms used along the document and describes the architecture of a Road ITS system based on GNSS as it is intended in this standard. This EN does not address: - the performance metrics to be used to define the Road ITS system performance requirements, highly depending on the use case and the will of the owner of the system; - the performance requirements of the various kinds of Road ITS systems; - the tests that are necessary to assess GBPT performance (field tests for this purpose will be addressed by EN 16803-2 and EN 16803-3).	Technical Committee CEN/C/CTC 5 - Space		standard	completed	Standard added to RDP as it was recommended by AW-Drones
2 UAS Traffic Management															
	U-space	Opinion 05-2019	Part 2(20), 3(21), and 4(17) UAS in class C1, C2, C3, if equipped with a network remote identification system it shall: (a) allow the upload of the UAS operator registration number in accordance with Article 14 of Implementing Regulation (EU) 2019/947 and exclusively following the process provided by the registration system. The system shall not accept an invalid UAS operator registration number; (b) ensure, in real time during the whole duration of the flight, the transmission from the UA using an open and documented transmission protocol, of at least the following data, in a way that it can be received through a network: i the UAS operator registration number; ii the unique serial number of the UA compliant with standard ANSI/CTA-2023-A; iii the time stamp, the geographical position of the UA and its height above the surface or take-off point; iv the route course measured clockwise from true north and ground speed of the UA; and v the geographical position of the remote pilot or, if not available, the take-off point; and (c) ensure that the user cannot modify the data mentioned under paragraph (b) points i, iii, iv and v.;	EASA	July-20	Open category and Specific	Opinion published								
								ISO TR 23629-1 - UAS Traffic Management (UTM) – Part 1: General requirements for UTM – Survey results on UTM	This project intends to start a survey on UTMs in each country, which is expected to reveal hundreds of commercial applications already in place, as well as social systems as their background conditions. Based on these results, we will analyze benefits and gaps for possible future standardization topics in consultation with authorities such as ICAO.	ISO/TC 20/SC 16/WG 4	sept-22	Technical Report	published		
								ISO 23629-7 - UAS Traffic Management (UTM) – Part 7: UTM data and information transfer at interface of traffic management integration system and UAS service suppliers – Data model related to spatial data for UAS and UTM	This standard specifies the data model that is related to various spatial information for common use between the operator for drone flight planning (UAS: Unmanned Aircraft System) and the system for operation control (UTM: UAS Traffic Management).	ISO/TC 20/SC 16/WG 4	Janv-22	Standard	ongoing	Will be published before 2022; currently showing limit date	
	Electronic Identification							ED-282 Minimum Operational Performance Specification for UAS e-Reporting	This document contains Minimum Operational Performance Standards (MOPS) for Unmanned Aircraft System (UAS) electronic reporting of UAS surveillance information (e-Reporting) for safety purposes. Compliance with this standard is recommended as one means of assuring that the equipment will perform its intended function(s) satisfactorily under all conditions normally encountered in routine aeronautical operation.	EUROCAE WG-105		standard	published	Title and description changed in v7.0	
M	U-space							F3548-21 UAS Traffic Management (UTM) UAS Service Supplier (USS) Interoperability Service	Revise UTM Standard to include UAM/AM PSU requirements for traffic management. This work will be included in V2.0 of WKS3418 •Define interoperability protocols and functional requirements for digital traffic management systems for Urban Air Mobility (UAM)•Focus on Provider of Services for UAM (PSU) and its necessary functions and interfaces. •Identify gaps in UTM Draft Standard: -UAM-specific entities (e.g., corridors) and updates/augmentations to UTM entities -Unique interfaces and integrations (e.g., Vertiports, Legacy ATM, UTM) -Flight planning, coordination, and execution as per UAM CONOPS -UAM-specific Contingency events •UAM Focus Group will operate in coordination with ongoing activities in the UTM Focus Group	ASTM F38.02	TBD	standard	published	WK63418 remains and continues advanced work on mixed use airspace.	
	U-space							F3411-19 Standard Specification for Remote ID and Tracking	Technical Interoperability & Protocols	ASTM F38 Unmanned Aircraft Systems		standard	published	superseded by F3411-22	

	U-space								AIR6388 Remote Identification and Interrogation of Unmanned Aerial Systems	The information presented in this AIR is intended to provide information about current remote identification methods and practical considerations for remotely identifying UAS. Depending on rigor and adherence requirements, Aerospace Standard (AS) and Aerospace Recommended Practice (ARP) documents may be developed. For example, ARPs may provide methods to remotely identify UAS using existing hardware technologies typically available to most consumers. ARPs may also specify the information exchange and message format between unmanned aerial systems and remote interrogation instruments. An AS, however, may highlight the wireless frequency band, message type, message encoding bits, and message contents.	SAE AS-4UCS Unmanned Systems (UAS) Control Segment Architecture	déc-18	information report	ongoing	
	U-space								Defines a message structure allowing transmitting the identification of a UAS as well as its the aircraft's current position. This data is required in order to establish the basic principles of UTM (UAS Traffic Management) which shall enable the safe integration of UAS into non-segregated airspace.	EUROCONTROL	avr-18	standard	published		
	Local E-identification	EU 2019/945	Part 2(12), 3(14) and 4(9) UAS in class C1, C2 and C3 shall have a direct remote identification that: (a) allows the upload of the UAS operator registration number in accordance with Article 14 of Implementing Regulation (EU) [20190517-120] and exclusively following the process provided by the registration system; (b) ensures, in real time during the whole duration of the flight, the direct periodic broadcast from the UA using an open and documented transmission protocol, of the following data, in a way that they can be received directly by existing mobile devices within the broadcasting range: i the UAS operator registration number; ii the unique physical serial number of the UA compliant with standard ANSICTA-2063; iii the geographical position of the UA and its height above the surface or take-off point; iv the route course measured clockwise from true north and ground speed of the UA; and v the geographical position of the remote pilot; (c) ensures that the user cannot modify the data mentioned under paragraph (b) points ii, iii, iv and v.	EASA	juin-19	open category and specific	Regulation applicable								Option 05-2019: UAS in class C1, C2, C3 shall have a direct remote identification system that: (a) allows the upload of the UAS operator registration number in accordance with Article 14 of Implementing Regulation (EU) 2019/947 and exclusively following the process provided by the registration system. The system shall not accept an invalid UAS operator registration number; (b) ensures, in real time during the whole duration of the flight, the direct periodic broadcast from the UA using an open and documented transmission protocol, of at least the following data, in a way that it can be received directly by existing mobile devices within the broadcasting range: i the UAS operator registration number; ii the unique serial number of the UA compliant with standard ANSICTA-2063-A; iii the time stamp, the geographical position of the UA; iv the time stamp, the remote identification add-on shall comply with the following: (1) allow the upload of the UAS operator registration number in accordance with Article 14 of Implementing Regulation (EU) 2019/947 and exclusively following the process provided by the registration system. The system shall not accept an invalid UAS operator registration number; (2) ensure, in real time during the whole duration of the flight, the direct periodic broadcast from the UA using an open and documented transmission protocol, of at least the following data, in a way that it can be received directly by existing mobile devices within the broadcasting range: (a) the UAS operator registration number; (b) the unique serial number of the UA compliant with standard ANSICTA-2063-A; (c) the time stamp, the geographical position of the UA.
	Local E-identification	EU 2019/945	Part 6(1, 3 and 4) A direct remote identification add-on shall comply with the following: (1) allows the upload of the UAS operator registration number in accordance with Article 14 of Implementing Regulation (EU) [20190517-120] and exclusively following the process provided by the registration system; (2) ensures, in real time during the whole duration of the flight, the direct periodic broadcast from the UA using an open and documented transmission protocol, of the following data, in a way that they can be received directly by existing mobile devices within the broadcasting range: i the UAS operator registration number; ii the unique physical serial number of the add-on compliant with standard ANSICTA-2063; iii the geographical position of the UA and its height above the surface or take-off point; iv the route course measured clockwise from true north and ground speed of the UA; and v the geographical position of the remote pilot or, if not available, the take-off point; (4) ensures that the user cannot modify the data mentioned under paragraph (3) points ii, iii, iv and v.	EASA	juin-19	open category and specific	Regulation applicable								
	Marking and Registration	EU 2019/947	Art 14(8) The UAS operators shall display their registration number on every unmanned aircraft meeting the conditions described in paragraph 5	EASA	juin-19	Open category and Specific	Regulation applicable from 1 July 2020								
	Marking and Registration							ASTM F2851-18 Standard Practice for UAS Registration and Marking (Excluding Small Unmanned Aircraft Systems)	This practice follows ICAO Annex 7 SARPS except in areas where the unique aspects of UAS may not allow compliance. In these cases, this document will address the issue and recommend the need for an alternate compliance method.	ASTM F38 Unmanned Aircraft Systems		standard	published	Renewed 2018	

	Geo-awareness	EU 2019/945	<p>Part 2(13), 3(15) and 4(10) UAS in class C1, C2 and C3 shall be equipped with a geo-awareness system that provides: (a) an interface to load and update data containing information on airspace limitations related to UA position and altitude imposed by the geographical zones, as defined by Article 15 of Implementing Regulation (EU) (20190517-120), which ensures that the process of loading or updating such data does not degrade its integrity and validity; (b) a warning alert to the remote pilot when a potential breach of airspace limitations is detected; and (c) information to the remote pilot on the UA's status as well as a warning alert when its positioning or navigation systems cannot ensure the proper functioning of the geo-awareness system</p>	EASA	jun-19	Open category and Specific	Regulation applicable								<p>opinion 05-2019: be equipped with a geo-awareness function that provides: (a) an interface to load and update data containing information on airspace limitations related to UA position and altitude imposed by the geographical zones, as defined by Article 15 of Implementing Regulation (EU) 2019/947, which ensures that the process of loading or updating such data does not degrade its integrity and validity; and (b) a warning alert to the remote pilot when a potential breach of airspace limitations is detected; and (c) information to the remote pilot on the UA's status as well as a warning alert when its positioning or navigation systems cannot ensure the proper functioning of the geo-awareness function;</p>
	Definition of zones	EU 2019/947	<p>Article 18 Operational conditions for UAS geographical zones 1. When defining UAS geographical zones for safety, security, privacy or environmental reasons, Member States may: (a) prohibit certain or all UAS operations, request particular conditions for certain or all UAS operations or request a prior operational authorisation for certain or all UAS operations; (b) subject UAS operations to specified environmental standards; (c) allow access only to UAS equipped with certain technical features, in particular remote identification systems or geo awareness systems. 2. On the basis of a risk assessment carried out by the competent authority, Member States may designate certain geographical zones in which UAS operations are exempt from one or more of the 'open' category requirements. 3. When pursuant to paragraphs 1 or 2 Member States define UAS geographical zones, for geo awareness purposes they shall ensure that the information on the UAS geographical zones, including their period of validity, is made publicly available in a common unique digital format.</p>	EASA	jun-19	Open category and Specific	Regulation applicable from 1 July 2020								
	U-space							MOPS for UAS Geo-Fencing	ED-269 "Minimum Operational Performance Standard for UAS geo-fencing" defining minimum requirements for the geo-fencing function at the level of individual components.	EUROCAE WG-105		standard	published		
	U-space							MOPS for UAS geo-caging	ED-270 "Minimum Operational Performance Standard for UAS geo-caging" defining minimum requirements for the geo-caging function at the level of individual components.	EUROCAE WG-105		standard	published		
	U-space							prEN4709-3 Aerospace series - Unmanned Aircraft Systems (UAS) - Security Requirements	<p>This European standard will provide means of compliance to cover geo-awareness related requirements for Part 2 to 4 of the delegated act. More specifically, the standard will provide requirements related to the main characteristics of the geo-awareness function, namely: -An interface to load and update data containing information on airspace limitations which ensures that the process of loading or updating of this data does not degrade its integrity and validity -A warning alert to the pilot when a potential breach of airspace limitations is detected -Information to the pilot on the UA's status as well as a warning alert when its positioning or navigation cannot ensure the proper functioning of the geo-awareness system In the context of this standard, geo-awareness is defined as an UAS function that warns the remote pilot if the UA is going to enter into an unauthorized zone. The standard will be developed in coordination with EUROCAEWG 105 / SG 33</p>	ASD-STAN D5WG8	sept-21	preEN / European standard	ongoing		
								WK69600 Surveillance UTM Supplemental Data Service Provider (SDSP) Performance	The objective is to define minimum performance standards for Surveillance Supplemental Data Service Providers (SDSP) equipment and services to UAS Service Suppliers/Providers (USS/USP) in a UAS Traffic Management (UTM) ecosystem. These surveillance services will provide aircraft track information to Detect and Avoid (DAA) systems to enable BLVOS UAS operations. Surveillance services may also support other USS capabilities such as counter-UAS. This standard will support spectrum radiationation equipment and installation approvals.	ASTM F38		Standard	ongoing		
								ISO/WD 23629-5	UTM – Part 5: UTM functional structure	ISO TC20 SC16	nov-21	Standard	ongoing		
								ISO/WD 23629-8	UTM – Part 8: Remote identification	ISO TC20 SC16	mai-21	Standard	ongoing		
								ISO/CD 23629-7	UTM – Part 7: Data model for spatial data	ISO TC20 SC17	janv-22	Standard	ongoing		
								ISO/23629-12	UTM – Part 12: Requirements for UTM services and service providers	ISO TC20 SC18	nov-22	Standard	ongoing		
M								EUROCAE Document	MOPS for U-Space Geo-awareness Service	EUROCAE WG-105 SG-3	Q2-2023	Standard	ongoing		
M								EUROCAE Document	MOPS for Traffic information / situation dissemination exchange format and service	EUROCAE WG-105 SG-3	Q1-2024	Standard	ongoing		
M								EUROCAE Document	MOPS for Flight Planning and Authorization Service for global awareness in AUTM in U-Space	EUROCAE WG-105 SG-3	Q1-2024	Standard	ongoing		
M								EUROCAE Document	MOPS for Network Identification Service of unmanned aerial vehicles for AUTM/U-Space	EUROCAE WG-105 SG-3	Q4-2022	Standard	On hold	Way forward being defined	

	C3 datalink and communication								AS6513 Unmanned Systems (UxS) Control Segment (UCS) Architecture Conformance Specification	This document is the authoritative specification within the SAE Unmanned Systems (UxS) Control Segment (UCS) Architecture for establishing conformance requirements for UCS products. The UCS products addressed by this specification are UCS software components and UCS software configurations that provide one or more UCS services, and UCS systems that employ one or more UCS services. The conformance of UCS products is determined by assessing the conformance of the UCS product description to the UCS Architecture. The UCS product description includes test artifacts.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		standard	published	
	C3 datalink and communication								AS6518 Unmanned Systems (UxS) Control Segment (UCS) Architecture UCS Architecture Model	This brief User Guide recaps the content of the AS6518 UCS Architectural Model described in detail in AS6512 UCS Architecture Architecture Description. The purpose of the UCS Architecture Model is to provide the authoritative source for other models and products within the UCS Architecture as shown in the AS6512 UCS Architecture Architecture Description. Preconditions for using the AS6518 EA Model include -access to / experience with Enterprise Architect 10 or higher, Corporate Edition. - experience with the Unified Modeling Language (UML) -installation of the [included] UCS_MDC.xml add in for Sparx Enterprise Architect per instructions below	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		standard	published	
	C3 datalink and communication								AS6522 Unmanned Systems (UxS) Control Segment (UCS) Architecture Architecture Technical Governance	The UCS technical governance comprises a set of policies, processes, and standard definitions to establish consistency and quality in the development of architecture artifacts and documents. It provides guidance for the use of adopted industry standards and modeling conventions in the use of Unified Modeling Language (UML) and Service Oriented Architecture Modeling Language (SoaML), including where the UCS Architecture deviates from normal UML conventions. This document identifies the defining policies, guidelines, and standards of technical governance in the following subjects: - industry standards adopted by the AS-4UCS Technical Committee; These are the industry standards and specifications adopted by AS-4UCS in the generation and documentation of the architecture. - UCS Architecture Development: UCS specific policies on the development of the UCS Architecture. The AS-4UCS Technical Committee governance policies are intentionally minimal. The object is to provide direction specific to the intent and scope of developing architecture artifacts that follow a consistent set of specifications and industry best practices. Standards are referenced within policies. Standards may place constraints on policies that are implemented by processes. Each process is intended to guide the development of architecture artifacts. For example, a standard may dictate that a UML diagram be modeled in a particular methodology using only approved stereotypes from the SoaML UML profile. UCS technical governance applies to the following technical work products that are generated within the AS-4UCS Technical Committee. It is not applicable to third party developers, programs, or any other consumer of the UCS Architecture.	SAE AS-4UCS Unmanned Systems (UxS) Control Segment Architecture		standard	published	
	Navigation								WKS8931 Evaluating AerialResponse RobotManeuvering: Maintain Position and Orientation	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions.support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28-Mar 2 2018 for adjudication of comments
	Navigation								WKS8932 Evaluating AerialResponse RobotManeuvering: Orbit a Point	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions.support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28-Mar 2 2018 for adjudication of comments
	Navigation								WKS8933 Evaluating AerialResponse RobotManeuvering: Avoid Static Obstacles	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions.support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	jun-18	standard	ongoing	
	Navigation								WKS8934 Evaluating AerialResponse RobotManeuvering: Pass Through Openings	A suite of standard test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions.support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28-Mar 2 2018 for adjudication of comments
	Navigation								WKS8935 Evaluating AerialResponse RobotManeuvering: Land Accurately (Vertical)	A suite of standards test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions.support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28-Mar 2 2018 for adjudication of comments
	C3 datalink and communication								WKS8942 Evaluating AerialResponse RobotRadio Communication Range: Line of Sight	A suite of standards test methods has been developed to measure maneuverability, endurance,communications, durability, logistics,autonomy, and safety to guide purchasing decisions.support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	Publication Delayed -Full Committee Meeting Feb 28-Mar 2 2018 for adjudication of comments

	C3 datalink and communication							WK58941 Evaluating Aerial Response Robot/Radio Communications Range Non Line of Sight	A suite of standards test methods has been developed to measure maneuverability, endurance, communications, durability, logistics, autonomy, and safety to guide purchasing decisions, support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	Publication Delayed - Full Committee Meeting Feb 28-Mar 2 2018 for adjudication of comments
	C3 datalink and communication							STANAG 4660 - Interoperable Command and Control Datalink for Unmanned Systems	Common standard Line-Of-Sight command and control data link for the safe and reliable operation of unmanned systems within a joint, coalition and controlled airspace operating environment.	NATO NNAG/JCGUAS		standard	published	
	Navigation							SAE6856 Improving Navigation Solutions Using Raw Measurements from Global Navigation Satellite System (GNSS) Receivers	This recommended practice provides users with the technical requirements and methods for accessing, viewing, and processing raw GNSS receiver measurements for improved unmanned vehicle navigation solutions.	SMCPNT Position, Navigation, and Timing Committee	mars-19	standard	ongoing	
	Navigation							SAE6857 Requirements for a Terrestrial Based Position, Navigation, and Timing (PNT) System to Improve Navigation Solutions and Ensure Critical Infrastructure Security	This recommended practice defines the technical requirements for a terrestrial-based PNT system to improve vehicle (e.g. unmanned, aerial, ground, maritime) positioning/navigation solutions and ensure critical infrastructure security, complementing GNSS technologies.	SMCPNT Position, Navigation, and Timing Committee	mars-19	standard	ongoing	
	C3 datalink and communication							MASPS on C3 Spectrum Management for the 5030/5091 MHz band	Minimum Aviation Systems Performance Standard defining requirements for the management of the 5030/5091 MHz band for use by C2 Link Services	EUROCAE WG-105	déc-20	standard	ongoing	
	C3 datalink and communication							Guidance on Spectrum Access, Use and Management	Guidance material describing considerations for the use of spectrum for UAS purposes	EUROCAE WG-105	mars-19	guidance	published	
	Cyber security	EU 2019/945	Part 3(8) and 4(12) UAS in class C2 and C3 shall be equipped with a data link protected against unauthorised access to the command and control functions.	EASA	jun-19	open	Regulation applicable							Opinion 05-2019 : unless tethered, be equipped with a command and control link protected against unauthorised access to the command and control functions.
	Cyber security							MASPS on RPAS C3 Security	Minimum Aviation Systems Performance Standard defining system level requirements for the application of Security measures to the UAS C3 Link	EUROCAE WG-105	jun-19	standard	on hold	
	C3 datalink and communication							Guidance on RPAS C3 security	Guidance material for the application of the MASPS listed above	EUROCAE WG-105	déc-19	guidance	on hold	
	C3 datalink and communication	EASA Decision	OSOR6 C3 link performance is appropriate for the operation	EASA	oct-19	Specific	published							
	C3 datalink and communication	EASA Decision	OSOR16 Multi crew coordination. (Criterion #3 Communication devices)	EASA	oct-19	Specific	published							
	C3 datalink and communication							MOPS	Minimum Operational Performance Specification for UAS Communications by Cellular Networks	EUROCAE WG-105 SG-2	Q2-2023	standard	ongoing	
	C3 datalink and communication							EUROCAE Report	UAS C2 MASPS European Stakeholders Report	EUROCAE WG-105 SG-2	Q2-2023	report	ongoing	
	C3 datalink and communication							ASTM	ASTM F1583-05 (2019): Standard Practice for Communications Procedures - Phonetics	ASTM		standard	published	Standard added to RDP as it was recommended by AW-Drones
4	Detect and Avoid													
M	Detect and avoid							EUROCAE Document ED-271	Minimum Aviation System Performance Standard for DAA (Traffic) in class A-C airspaces under IFR	EUROCAE WG-105	11/05/2022	standard	published	Published May 2022
	Detect and avoid							OSED	Operational Services and Environment Description for DAA for DAA in Class D-G airspaces under VFR/IFR	EUROCAE WG-105	janv-19	standard	published	
	Detect and avoid							MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for DAA against conflicting traffic for RPAS operating under IFR and VFR in all airspace classes	EUROCAE WG-105	Q2-2023	standard	ongoing	target date changed
	Detect and avoid							MOPS	Minimum Operational Performance Standard (Requirements at equipment level) for DAA against conflicting traffic for RPAS operating under IFR and VFR in all airspace classes	EUROCAE WG-105	Q2-2024	standard	ongoing	planned changed to ongoing
	Detect and avoid							OSED	ED-267 Operational Services and Environmental Description for DAA in very Low Level Operations	EUROCAE WG-105	jun-20	standard	published	

	Detect and avoid								MOPS	Minimum Operational Performance Standard (Requirements at equipment level) for DAA at Very Low Level (VLL)	EUROCAE WG-105	Q2-2024	standard	ongoing	target date changed
	Detect and avoid								STANREC 4811 Ed. 1/ AEP- 101 Ed. A Ver. 1 "UAS sense and avoid"	To detail comprehensive guidance and recommended practice for the development of Sense and Avoid systems, referencing and providing guidance regarding application of existing standards and best practice.	NATO FINAS	Feb-18	guide	published	
	Detect and avoid								F3442-20 Specification for Detect and Avoid Performance Requirements	Defines minimum performance standards Comprehensive DAA Standard under annex to define test methods AND minimum performance standards for DAA systems and sensors applicable to smaller UAS BLVOS operations for the protection of manned aircraft in lower altitude airspace	ASTM F38 Unmanned Aircraft Systems		standard	published	Publication expected
	Detect and avoid								WK62669 Test Method for DAA	Covering systems and sensors Comprehensive DAA Standard under annex to define test methods AND minimum performance standards for DAA systems and sensors applicable to smaller UAS BLVOS operations for the protection of manned aircraft in lower altitude airspace	ASTM F38 Unmanned Aircraft Systems	jun-19	standard	ongoing	Working Group formed under terms of reference. Number changed to WK62669 instead of WK62668
	Detect and avoid								EUROCAE Report	European Industry Position Report on RTCA SC-147 ACAS xXu	EUROCAE WG-105	d6c-22	report	ongoing	
	Detect and avoid								RTCA	RTCA DO-365: MOPS for Detect and Avoid (DAA) Systems - Phase 1	RTCA SC-228	May-2017	standard	published	Standard added to RDP as it was recommended by AW-Drones
	Detect and avoid								RTCA	RTCA DO-366: Minimum Operational Performance Standards (MOPS) for Air-to-Air Radar for Traffic Surveillance	RTCA SC-228	May-2017	standard	published	Standard added to RDP as it was recommended by AW-Drones
	Detect and avoid								EUROCAE and RTCA	ED-275 Vol. 1/ RTCA DO-386: Minimum Operational Performance Standards for Airborne Collision Avoidance System Xu (ACAS Xu)	EUROCAE		standard	published	Standard added to RDP as it was recommended by AW-Drones
5	RPAS Automation														
	Development assurance (Software)								ASTM F3269 Standard Practice for Methods to Safely Bound Flight Behavior of Unmanned Aircraft Systems Containing Complex Functions	This standard practice defines design and test best practices that if followed, would provide guidance to an applicant for providing evidence to the civil aviation authority (CAA) that the flight behavior of an unmanned aircraft system (UAS) containing complex function(s) is constrained through a run-time assurance (RTA) architecture to maintain an acceptable level of flight safety.	ASTM F38 Unmanned Aircraft Systems		standard	published	FAA Notice Of Availability (NOA) Pending approval of ASTM WK57659 as foundational document
M	Automatic modes, takeoff, Landing, taxing								ASTM F3269-21 Standard Practice for Methods to Safely Bound Flight Behavior of Aircraft Systems Containing Complex Functions Using Run-Time Assurance	Goal is to develop the standard to a level of capability that defines run-time monitoring (RTA) attributes to a level that the FAA or CAA will agree that monitors developed to this standard are sufficient to allow the UAS to evolve the complex function with its associated avionics equipment and sensors without requiring vehicle recertification as the CONOPS evolve after initial certification. a. Provide additional guidance on Safety Monitor design best practices, to explicitly include guidance on partitioning, dissimilarity, and the option for multiple individual safety monitors comprising the Safety Monitor function, as well as defining safety monitor classes and key attributes. b. Provide additional use cases as Appendices. c. Provide additional information contrasting the F3269 approach with other architectural approaches (e.g., SAE ARP 4754A, RTCA DO-178C). d. Modify requirements to performance based to allow multiple implementation and implementation architectures e. Make additional updates as required.	ASTM F38.01		standard	published	
	Automatic modes, takeoff, Landing, taxing								ED-252 OSED	Operational Services and Environment Description for Automatic Take-Off and Landing.	EUROCAE WG-105		standard	published	
	Automatic modes, takeoff, Landing, taxing								MASPS	ED-283 Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for Automatic Take-Off and Landing	EUROCAE WG-105	jun-20	standard	published	
	Automatic modes, takeoff, Landing, taxing								ED-251 OSED	Operational Services and Environment Description for Automatic Taxing	EUROCAE WG-105		standard	published	
	Automatic modes, takeoff, Landing, taxing								MASPS	Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for Automatic Taxing	EUROCAE WG-105	jun-20	standard	published	
	Emergency recovery/terminations systems	EU 2019/945	Parts 2(7), 3(7) and 4(6) A UAS Class C1, C2 and C3 shall: in case of a loss of data link, have a reliable and predictable method for the UA to recover the data link or terminate the flight in a way that reduces the effect on third parties in the air or on the ground.	EASA	jun-19	open category and specific	Regulation applicable								Opinion 05-2019: in case of a loss of the command and control link, have a reliable and predictable method for the UA to recover the command and control link or terminate the flight in a way that reduces the effect on third parties in the air or on the ground.

	Emergency recovery/terminations systems									ED-253 OSED	Operational Services and Environment Description for Automation and Emergency Recovery	EUROCAE WG-105	déc-18	standard	published	
	Emergency recovery/terminations systems									MASPS	ED-281 Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for automation and Emergency Recovery	EUROCAE WG-105	jun-20	standard	published	
6	Design & Airworthiness															
	Development assurance (Software)									ASTM F3151 Standard Specification for Verification of Avionics Systems1	This specification provides a process by which the intended function and compliance with safety objectives of avionics systems may be verified by system-level testing. Software and hardware development assurance are not in the scope of this specification and this specification should not be used if a development assurance process is required.	ASTM F39 Aircraft Systems		standard	published	This will be reference in AC for Special Class §21.17(b) To be uses where appropriate in lieu of DO 178. NEW DELIVERABLE
	UA Design and Airworthiness									AS6009A JAUS Mobility Service Set	This document defines a set of standard application layer interfaces called JAUS Mobility Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Mobility Services represent the vehicle platform-independent capabilities commonly found across all domains and types of unmanned systems (referred to as UAVs). At present, over 15 services are defined in this document many of which were updated in this revision to support Unmanned Underwater Vehicles (UUVs).	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness									AS5684B JAUS Service Interface Definition Language	The SAE Aerospace Information Report AIR5315 – Generic Open Architecture (GOA) defines "a framework to identify interface classes for applying open systems to the design of a specific hardware/software system." (see JAUS Service (Interface) Definition Language defines an XML schema for the interface definition of services at the Class 4L, or Application Layer, and Class 3L, or System Services Layer, of the Generic Open Architecture stack (see Figure 1). The specification of JAUS services shall be defined according to the JAUS Service (Interface) Definition Language document.	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness									AS6062 JAUS Mission Spooling Service Set	This document defines a set of standard application layer interfaces called JAUS Mission Spooling Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Mission Spooling Services represent the platform-independent capabilities commonly found across all domains and types of unmanned systems. At present, 1 service is defined in this document (more services are planned for future versions of this document): • Mission Spooler: Stores mission plans, coordinates mission plans, and parcels out elements of the mission plan for execution The Mission Spooler service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. The JSD is fully compliant with the JAUS Service Interface Definition Language (JSIDL).	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	UA Design and Airworthiness									AS6060 JAUS Environment Sensing Service Set	This document defines a set of standard application layer interfaces called JAUS Environment Sensing Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Environment Sensing Services represent typical environment sensing capabilities commonly found across all domains and types of unmanned systems in a platform-independent manner. At present, five services are defined in this document: • Range Sensor: Determine the proximity of objects in the platform's environment • Visual Sensor: Provides common configuration and setup for different types of imaging systems • Digital Video: A type of Visual Sensor that manages digital video • Analog Video: A type of Visual Sensor that manages analog video • Still Image: A type of Visual Sensor that manages and encodes individual digital images Each service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. Each JSD is fully compliant with the JAUS Service Interface Definition Language (AS5684).	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	
	HMI									AS6040 JAUS HMI Service Set	This document defines a set of standard application layer interfaces called JAUS HMI Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The HMI Services represent the platform-independent Human Machine Interface (HMI) capabilities commonly found across all domains and types of unmanned systems. Five services are defined in this document: • Drawing • Parking Device • Keyboard • Digital Control • Analog Control Each service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. Each JSD is fully compliant with the JAUS Service Interface Definition Language (JSIDL) (AS5684).	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee		standard	published	

	UA Design and Airworthiness									AS5710A JAUS Core Service Set	This document defines a set of standard application layer interfaces called JAUS Core Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Core Services represent the infrastructure commonly found across all domains and types of unmanned systems. At present, eight services are defined in this document: • Transport Service: Abstracts the functionality of the underlying communication transport layer • Events Service: Establishes a publish/subscribe mechanism for automatic messaging • Access Control: Manages preemptible exclusive control for safety critical operations • Management: Defines component life-cycle management • Time: Allows clients to query and set the system time for the component • Liveness: Provides a means to maintain connection liveness between communicating components • Discovery: Governs automatic discovery of remote entities and their capabilities • List Manager: Encompasses behavior common to doubly linked lists Each service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. Each JSD is fully compliant with the JAUS Service Interface Definition Language [JSIDL].	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published
	UA Design and Airworthiness									ARP6012A JAUS Compliance and Interoperability Policy	This document, the JAUS Compliance and Interoperability Policy (ARP6012), recommends an approach to documenting the complete interface of an unmanned system or component in regard to the application of the standard set. While non-SAE AS-4 JAUS documents are referenced in this ARP they are not within the scope of this document and should be viewed as examples only.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		recommended practice	published
	UA Design and Airworthiness									AIR5645A JAUS Transport Consideration	This SAE Aerospace Information Report (AIR) discusses characteristics of data communications for the Joint Architecture for Unmanned Systems (JAUS). This document provides guidance on the aspects of transport media, unmanned systems and the characteristics of JAUS itself that are relevant to the definition of a JAUS transport specification.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		information report	published
	UA Design and Airworthiness									AS5669A JAUS/SDP Transport Specification	This SAE Aerospace Standard (AS) specifies a data communications layer for the transport of messages defined by the Joint Architecture for Unmanned Systems (JAUS) or other Software Defined Protocols (SDP). This Transport Specification defines the formats and protocols used for communication between compliant entities for all supported link-layer protocols and media. Although JAUS is the SDP used as the example implemented throughout this document, AS5669 can be used for any SDP that meets the required capabilities. A Software Defined Protocol is defined as an application data interface for communicating between software elements. The SDP is agnostic of the underlying communications protocol and in fact communicates in much the same manner regardless if the communicating entities are collocated in the same memory space or separated by a satellite link.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published
	UA Design and Airworthiness									AS6091 JAUS Unmanned Ground Vehicle Service Set	This document defines a set of standard application layer interfaces called JAUS Unmanned Ground Vehicle Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Unmanned Ground Vehicle Services represent the platform-specific capabilities commonly found in UGVs, and augment the Mobility Service Set [AS6009] which is platform-agnostic. At present ten (10) services are defined in this document.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published
	UA Design and Airworthiness									AS6057A JAUS Manipulator Service Set	This document defines a set of standard application layer interfaces called JAUS Manipulator Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Manipulator Services represent platform-independent capabilities commonly found across domains and types of unmanned systems. At present, twenty-five (25) services are defined in this document.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published
	UA Design and Airworthiness									ARP6227 JAUS Messaging over the OMG Data Distribution Service (DDS)	This document defines a standard representation of JAUS AS5684A message data in DDS IDL defined by the Object Management Group (OMG) CORBA 3.2 specification. This document does NOT address how JAUS transport considerations or JAUS service protocols are implemented on OMG DDS platforms.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		recommended practice	published
	UA Design and Airworthiness									AIR5665B Architecture Framework for Unmanned Systems	This SAE Aerospace Information Report (AIR) describes the Architecture Framework for Unmanned Systems (AFUS). AFUS comprises a Conceptual View, a Capabilities View, and an Interoperability View. The Conceptual View provides definitions and background for key terms and concepts used in the unmanned systems domain. The Capabilities View uses terms and concepts from the Conceptual View to describe capabilities of unmanned systems and of other entities in the unmanned systems domain. The Interoperability View provides guidance on how to design and develop systems in a way that supports interoperability.	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		information report	published
	UA Design and Airworthiness									AIR5664A JAUS History and Domain Model	The purpose of this SAE Aerospace Information Report (AIR) is two-fold: to inform the reader of the extent of effort that went into the development of the Joint Architecture for Unmanned Systems (JAUS) and to capture for posterity the domain analysis that provides the underpinnings for the work by the AS-4 Committee (Unmanned Systems).	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		information report	published
	UA Design and Airworthiness									AS6062A JAUS Mission Spooling Service Set	This document defines a set of standard application layer interfaces called JAUS Mission Spooling Services. JAUS Services provide the means for software entities in an unmanned system or system of unmanned systems to communicate and coordinate their activities. The Mission Spooling Services represent the platform-independent capabilities commonly found across all domains and types of unmanned systems. At present, 1 service is defined in this document (more services are planned for future versions of this document): • Mission Spooler: Stores mission plans, coordinates mission plans, and parcels out elements of the mission plan for execution The Mission Spooler service is described by a JAUS Service Definition (JSD) which specifies the message set and protocol required for compliance. The JSD is fully compliant with the JAUS Service Interface Definition Language [JSIDL].	SAE AS-4JAUS Joint Architecture for Unmanned Systems Committee		standard	published

	UA Design and Airworthiness								AS6111 JAUS Unmanned Maritime Vehicle Service Set	This document defines a message-passing interface for services representing the platform-specific capabilities common across unmanned maritime vehicles.	SAE AS-4/JAUS Joint Architecture for Unmanned Systems Committee	juli-19	standard	ongoing	
	UA Design and Airworthiness								AS6971 Test Protocol for UAS Reciprocating (Intermittent) Engines as Primary Thrust Mechanism	This standard is intended to provide a method (or methods) to obtain repeatable and consistent measurements to reflect true engine performance and durability in customer. Standardized methodology is needed to normalize engine performance to fairly rate engine operating variables and parameters. Operational protocols will be defined according to engine class and will be based on those developed for on-highway applications. Based on typical engine operation, a series of speed and load combinations and/or sequences will be determined. The scope will include dynamometer based testing and static propeller-based experiments. The industry consists of many platforms that use reciprocating engines as the main (or sole) provider of rotational energy to propeller. There also exists a significant move towards hybrid-based engine-battery systems that are expected to have different operational requirements. This standard will focus on those using the engine as the main thrust provider, but allowances will also be considered for hybrid designs. The scope will include power correction methodologies to provide a more accurate description of performance.	SAE E-39 Unmanned Aircraft Propulsion Committee	mai-19	standard	ongoing	
	UA Design and Airworthiness								AS#### Ground support equipment (preheaters, starters, fuel pumps, fuel couplings, fuel mixing, fuel filters, preflight weight/balance, bore-sighting of payload, storage containers, alignment hardware, wheel chocks, "remove before flight" items, electronic and software links.		SAE E-39 Unmanned Aircraft Propulsion Committee	juni-19	standard	planned	
	UA Design and Airworthiness								AS#### Propeller hubs		SAE E-39 Unmanned Aircraft Propulsion Committee	juli-19	standard	planned	
	UA Design and Airworthiness								ARP#### Propeller Information Report		SAE E-39 Unmanned Aircraft Propulsion Committee	aoct-19	information report	ongoing	
	UA Design and Airworthiness								AIR6962 Ice Protection for Unmanned Aerial Vehicles	A review of icing materials that would be educational to a designer of a UAV ice protection system is provided. Additionally, the differences between unmanned and manned ice protection systems are explored along with a discussion on how these differences can be addressed.	SAE AC-9C Aircraft Icing Technology Committee	dec-18	information report	ongoing	
	UA Design and Airworthiness								ARP94010 Aerospace - Vehicle Management Systems - Flight Control Design, Installation and Test of, Military Unmanned Aircraft, Specification Guide For	This document establishes recommended practices for the specification of general performance, design, test, development, and quality assurance requirements for the flight control related functions of the Vehicle Management Systems (VMS) of military Unmanned Aircraft (UA), the airborne element of Unmanned Aircraft Systems (UAS), as defined by ASTM F 2395-07. The document is written for military unmanned aircraft intended for use primarily in military operational areas. The document also provides a foundation for considerations applicable to safe flight in all classes of airspace.	SAE A-6 Aerospace Actuation, Control and Fluid Power Systems		recommended practice	published	
	UA Design and Airworthiness								ARP5724 Aerospace - Testing of Electromechanical Actuators, General Guidelines For	This document provides an overview of the tests, and issues related to testing, that are unique to Electromechanical Actuators (EMAs). The tests, and issues documented, are not necessarily all-inclusive. This document discusses both the tests applicable to EMAs and the test methodologies to accomplish the test objectives. EMAs may be used in a wide variety of applications such as utility, secondary flight controls and primary flight controls, in a wide variety of markets including manned and unmanned civil and military aircraft, small missile fin and thrust vector control applications up to high powered utility and flight controls. EMAs may also have either a rotary or a linear output, be servo controlled or use simple open loop point-to-point or other control topologies. As such this document covers a wide range of potential applications, the application of any given test requirement is determined by the application and the user. This document attempts to provide basic guidance on which tests should be considered for various applications. This document also lists tests that are not unique to EMAs, but are still applicable to EMAs. In these instances a discussion of such tests is not contained in this document, and as applicable, the reader may reference the appropriate documents as indicated in the text. While many EMA configurations include digital power drive electronics (PDE), the specific tests required for the electronic hardware, software, or firmware are outside the scope of this document.	A-6 Aerospace Actuation, Control and Fluid Power Systems		recommended practice	published	
	UA Design and Airworthiness								AIR744™ Aerospace Auxiliary Power Sources	This SAE Aerospace Information Report (AIR) is a review of the general characteristics of power sources that may be used to provide secondary, auxiliary, or emergency power for use in aircraft, space vehicles, missiles, remotely piloted vehicles, air cushion vehicles, surface effect ships, or other vehicles in which aerospace technology is used. The information contained herein is intended for use in the selection of the power source most appropriate to the needs of a particular vehicle or system. The information may also be used in the preparation of a power source specification. Considerations for use in making a trade study and an evaluation of the several power sources are included. More detailed information relating to specific power sources is available in other SAE Aerospace Information Reports or in Aerospace Recommended Practices.	A-6 Aerospace Actuation, Control and Fluid Power Systems		information report	published	

	UA Design and Airworthiness								ASS0881F Wiring Aerospace Vehicle	This specification covers all aspects in electrical wire interconnection systems (EWS) from the selection through installation of wiring and wiring devices and optical cabling and termination devices used in aerospace vehicles. Aerospace vehicles include manned and unmanned airplanes, helicopters, lighter-than-air vehicles, missiles and external pods.	SAE AE-34 Elec Wiring and Fiber Optic Interconnect Sys Install Committee		standard	published	
	UA Design and Airworthiness								ASS0881G Wiring Aerospace Vehicle	This specification covers all aspects in electrical wire interconnection systems (EWS) from the selection through installation of wiring and wiring devices and optical cabling and termination devices used in aerospace vehicles. Aerospace vehicles include manned and unmanned airplanes, helicopters, lighter-than-air vehicles, missiles and external pods.	SAE AE-34 Elec Wiring and Fiber Optic Interconnect Sys Install Committee	d6c-18	standard	ongoing	
	UA Design and Airworthiness								AS### Artificial simulant standards for drone or FOD impact/ingestion	planned	SAE G-28 Simulants for Impact and Ingestion Testing	d6c-19	standard	planned	
	Emergency recovery/terminations systems								F3322-18 Standard Specification for Small Unmanned Aircraft System (sUAS) Parachutes	This specification covers the design and manufacture requirements for deployable parachutes of small unmanned aircraft (sUA). This specification defines the design, fabrication, and test requirements of installable, deployable parachute recovery systems (PRS) that are designed to be integrated into a sUA to lessen the impact energy of the system should the sUA fail to sustain normal stable safe flight. Compliance with this specification is intended to support an applicant in obtaining permission from a civil aviation authority (CAA) to fly a sUA over people.	ASTM F38 Unmanned Aircraft Systems	Sept-18	specification	Published	
	UA Design and Airworthiness								F2490-05(2013) Standard Guide for Aircraft Electrical Load and Power Source Capacity Analysis	This guide covers how to prepare an electrical load analysis (ELA) to meet Federal Aviation Administration (FAA) requirements.	ASTM F39 Aircraft Systems		standard	published	Light Sport Aircraft guidance will be revised to apply to UAS.
	maintenance								F2799-14 Standard Practice for Maintenance of Aircraft Electrical Wiring Systems	Damaged wiring or equipment in an aircraft, regardless of how minor it may appear to be, cannot be tolerated. It is, therefore, important that maintenance be accomplished using the best techniques and practices to minimize the possibility of failure.	ASTM F39 Aircraft Systems		standard	published	
M	UA Design and Airworthiness								F3563-22 Specification for Design and Construction of Large Fixed Wing Unmanned Aircraft Systems	To develop an ASTM design and construction standard for larger mass fixed-wing Unmanned Aerial Systems (UAS). Design and Construct Standards are currently in existence for Part 23 General Manned Aircraft as well as for Fixed Wing and VTOL Small UAS (sUAS). There currently exists a gap for Part 23 General Aircraft of the Large Fixed Wing Unmanned Variety. This ASTM standard will serve to fill that gap by including design and construct requirements, best practices, and proposed methods of compliance specific to Large UAS (up to 19,000 lbs).	ASTM F38.01	jun-19	standard	published	Fill industry identified gaps required for the design and construction of UAS under Part 21 or 23
	UA Design and Airworthiness								ASTM F2910-14 Standard Specification for Design and Construction of a Small Unmanned Aircraft System (sUAS)	This specification establishes the design, construction, and test requirements for a small unmanned aircraft system (sUAS). It is intended for all sUAS that are permitted to operate over a defined area and in airspace authorized by a nation's governing aviation authority (GAA). Unless otherwise specified by a nation's GAA, this specification applies only to UA that have a maximum takeoff gross weight of 55 lb/25 kg or less.	ASTM F38 Unmanned Aircraft Systems		standard	published	This will be reference in AC for Special Class §21.17(D)
	UA Design and Airworthiness								F3298-19 Standard Specification for Design, Construction, and Verification of Lightweight Unmanned Aircraft Systems (UAS)	This specification covers the airworthiness requirements for the design of fixed-wing unmanned aircraft systems. This specification defines the baseline design, construction, and verification requirements for an unmanned aircraft system (UAS)	ASTM F38 Unmanned Aircraft Systems		standard	published	Title change
	UA Design and Airworthiness								ASTM WK63678/ WK64619 Revision of F3298 - 18 Standard Specification for Design, Construction, and Verification of Fixed-Wing Unmanned Aircraft Systems (UAS)	The initial standard only addressed Fixed-Wing UAS. Response from the FAA required both vertical lift and fixed-wing in order to be accepted as a method of compliance for UAS airworthiness certification in the forthcoming advisory circular for 21-17(b). This required a rapid-action reorganization of the standard, inclusion of VTOL-specific items and a title change.	ASTM F38 Unmanned Aircraft Systems	19-nov	standard	In progress	Ballot pending Sub-Committee approval
	Manufacturer organisation								ASTM F2911-14e1 Standard Practice for Production Acceptance of Small Unmanned Aircraft System (sUAS)	This standard defines the production acceptance requirements for a small unmanned aircraft system (sUAS). This standard is applicable to sUAS that comply with design, construction, and test requirements identified in Specification F2910. No sUAS may enter production until such compliance is demonstrated.	ASTM F38 Unmanned Aircraft Systems		standard	published	
	Manufacturer organisation								ASTM F3003-14 Standard Specification for Quality Assurance of a Small Unmanned Aircraft System (sUAS)	This standard defines the quality assurance requirements for the design, manufacture, and production of a small unmanned aircraft system (sUAS).	ASTM F38 Unmanned Aircraft Systems		standard	published	
	Batteries/fuel cell power generating system								WKWK60937 Standard Specification for design of Fuel Cells for Use in Unmanned Aircraft Systems (UAS)	This standard will outline specification for the use of fuel cell power generating systems for application in UAS.	ASTM F38 Unmanned Aircraft Systems	TBD	standard	ongoing	

	Development assurance (Software)								ASTM F3201-16 Standard Practice for Ensuring Dependability of Software Used in Unmanned Aircraft Systems (UAS)	This standard practice intends to ensure the dependability of UAS software. Dependability includes both the safety and security aspects of the software. This practice will focus on the following areas: (a) Organizational controls (for example, management, training) in place during software development. (b) Use of the software in the system, including its architecture and contribution to overall system safety and security. (c) Metrics and design analysis related to assessing the code. (d) Techniques and tools related to code review. (e) Quality assurance. (f) Testing of the software.	ASTM F38 Unmanned Aircraft Systems		standard	published	
	UA Design and Airworthiness							ASTM WK16285 New Specification for Design and Performance of an Unmanned Aircraft System-Class 1320 (550# Gross Weight to 1320# Gross Weight)	The specification covers airworthiness requirements for an acceptable powered fixed wing aircraft UAS.	ASTM F38 Unmanned Aircraft Systems	TBD	standard	ongoing	This work item will be continued using guidelines from ASTM F37 Light Sport Aircraft Committee	
	maintenance							ASTM F2909-14 Standard Practice for Maintenance and Continued Airworthiness of Small Unmanned Aircraft Systems (sUAS)	This standard is written for all sUAS that are permitted to operate over a defined area and in airspace authorized by a nation's governing aviation authority (GAA). It is assumed that a visual observer(s) will provide for the sense and avoid requirement to avoid collisions with other aircraft and that the maximum range and altitude at which the sUAS can be flown will be specified by the nation's GAA. Unless otherwise specified by a nation's GAA this standard applies only to UA that have a maximum take off gross weight of 25 kg (55 lb) or less. The sUAS shall be maintained for continued airworthiness to meet UAS limitations and performance capabilities required by the nation's GAA.	ASTM F38 Unmanned Aircraft Systems		standard	published	Updated revision underway under WK WK63991	
	UA Design and Airworthiness							prEN4709-1 Aerospace series - Unmanned Aircraft Systems (UAS) - Product and Verification Requirements	This European standard will provide means of compliance to cover Part 1 to 5 of the delegated act annex. This includes compliance with product requirements for all UAS authorized to operate in the 'open' category (class C0, C1, C2, C3 and C4 UAS). This document does not cover "Specific" or "Certified" category of UAS. Compliance with this document assists in complying with CE marking technical requirements and covers, but is not limited to, physical and mechanical properties, flammability, electrical properties, functional safety, software, readability of the instructions and manual etc. Additional hazards that occur from the characteristics of third party payloads are excluded.	ASD-STAN D5WG8	d6c-21	preEN / European standard	ongoing		
								Guidelines	ED-280 Guidelines for UAS safety analysis for the Specific category (low and medium levels of robustness)	EUROCAE WG-105	Jun 20	Guidance	published		
	Ground control station							MASPS	ED-272 Minimum Aviation System Performance Standard (End-to-end Requirements at system level) for the Remote Pilot Station interface to Air Traffic Control (ATC).	EUROCAE WG-105	Jun-20	standard	published		
M								EUROCAE Document ED-301	Guidelines for the Use of Multi-GNSS Solutions for UAS Specific Category - Low Risk Operations SAIL I and II	EUROCAE WG-105 SG-6	01/09/2022	standard	published		
A								EUROCAE document	Guidelines for the Use of Multi-GNSS Solutions for UAS - Medium Risk	EUROCAE WG-105 SG-6	Q2-2024	standard	ongoing		
								EUROCAE Document	Guidelines on the automatic protection of the flight envelope from human errors for UAS	EUROCAE WG-105 SG-6	Q1-2024	standard	ongoing		
	Emergency recovery/terminations systems	Opinion 05-2019	Part 16(6) and 16(7) UAS in class C5 and C6 shall provide the remote pilot with means to continuously monitor the quality of the command and control link and receive an alert when it is likely that the link is going to be lost or degraded to the extent of compromising the safe conduct of the operation, and another alert when the link is lost	EASA	jun-20	Specific	Opinion published								
	UA Design and Airworthiness	EU 2019/945	Part 1(3) UAS in Class C0 shall have a maximum attainable height above the take-off point limited to 120 m;	EASA	jun-19	open	Regulation applicable								
	UA Design and Airworthiness	EU 2019/945	Parts 2(3), 3(2) and 4(2) UAS in Class C1, C2 and C3 shall have a maximum attainable height above the take-off point limited to 120 m or be equipped with a system that limits the height above the surface or above the take-off point to 120 m or to a value selectable by the remote pilot. If the value is selectable, clear information about the height of the UA above the surface or take-off point during flight shall be provided to the remote pilot.	EASA	jun-19	open	Regulation applicable								
	UA Design and Airworthiness	EU 2019/945	Parts 1(7) and 2(17) UAS in Class C0 and C1 shall, if equipped with a follow-me mode and when this function is on, be in a range not exceeding 50 m from the remote pilot, and make it possible for the remote pilot to regain control of the UA;	EASA	jun-19	open	Regulation applicable								
	Manufacturer organisation							ISO 21384-2 - Requirements for ensuring the safety and quality of the design and manufacture of UAS	Requirements for ensuring the quality and safety of the design and manufacture UAS. It includes information regarding the UA, any associated remote control station(s), the C2 links, any other required data links and any other system elements as may be required.	ISO TC20/SC16/WG2	nov-20	standard	ongoing		

UA Design and Airworthiness								STANAG 4671 "UAV System Airworthiness Requirements (USAR)" (Fix wing UAV, MTOW<=1 50Kg).	Set of technical airworthiness requirements intended primarily for the airworthiness certification of fixed-wing military UAVs with a maximum take-off weight between 150 and 20,000 kg that intend to regularly operate in non-segregated airspace	NATO FINAS				published
UA Design and Airworthiness								STANAG 4702 "Rotary Wing Unmanned Aerial Systems Airworthiness Requirements" (Rotorcraft UAV, 150Kg<MTOW<= 3125Kg)	set of technical airworthiness requirements intended for the airworthiness certification of rotary-wing military UAV Systems with a maximum take-off weight between 150 and 3175 kg that intend to regularly operate in non-segregated airspace	NATO FINAS				published
UA Design and Airworthiness								STANAG 4703 "Light Unmanned Aircraft Systems Airworthiness Requirements" (Fix wing UAV, 150Kg<MTOW)	Minimum set of technical airworthiness requirements intended for the airworthiness certification of fixed-wing Light UAVs with a maximum take-off weight not greater than 150 kg and an impact energy greater than 66 J (49 ft-lb) that intend to regularly operate in non-segregated airspace	NATO FINAS				published
UA Design and Airworthiness								STANAG 4746 "Unmanned Aerial Vehicle System Airworthiness Requirements for Light Vertical Take Off and Landing Aircraft"	Set of technical airworthiness requirements intended for the airworthiness certification	NATO FINAS	2018			ongoing
UA Design and Airworthiness	EU 2019/945	Parts 1(5), 3(6) and 4(6) UAS in Class C0, C1 and C2 shall be designed and constructed in such a way as to minimise injury to people during operation, sharp edges shall be avoided, unless technically unavoidable under good design and manufacturing practice. If equipped with propellers, it shall be designed in such a way as to limit any injury that may be inflicted by the propeller blades.	EASA	jun-19	open	Regulation applicable								
UA Design and Airworthiness	EU 2019/945	Parts 2(15), 3(17) and 4(13) A UAS Class C1, C2 and C3 shall provide the remote pilot with clear warning when the battery of the UA or its control station reaches a low level so that the remote pilot has sufficient time to safely land the UA.	EASA	jun-19	open	Regulation applicable								
UA Design and Airworthiness	EU 2019/945	Parts 2(5) and 3(4) UAS in class C1 and C2 shall have the requisite mechanical strength, including any necessary safety factor, and, where appropriate, stability to withstand any stress to which it is subjected to during use without any breakage or deformation that might interfere with its safe flight.	EASA	jun-19	open	Regulation applicable								
UA Design and Airworthiness	EU 2019/945	Parts 2(16), 3(18) and 4(14) UAS in Class C1, C2 and C3 shall be equipped with lights for the purpose of: (a) the controllability of the UA, (b) the conspicuity of the UA at night, the design of the lights shall allow a person on the ground, to distinguish the UA from a manned aircraft.	EASA	jun-19	open	Regulation applicable								requirement also to specific category when operated in VLLC: be equipped: (a) with lights for the purpose of controllability of the UA; and (b) with at least one green flashing light for the purpose
UA Design and Airworthiness							ARP6336 Lighting Applications for Unmanned Aircraft Systems (UAS)	This SAE Aerospace Recommended Practice (ARP) provides technical recommendations for the application, design and development of lighting for Unmanned Aircraft (UA). The recommendations set forth in this document are to aid in the design of UA lighting for the type or size of aircraft and the operation in the National Aerospace System for which the aircraft is intended.	SAE A-20 Aircraft Lighting Committee	dec-18	Recommended Practice	ongoing	ongoing	
UA Design and Airworthiness	EU 2019/945	Part 2(1) UAS in class C1 shall be made of materials and have performance and physical characteristics such as to ensure that in the event of an impact at terminal velocity with a human head, the energy transmitted to the human head is less than 80 J, or, as an alternative, shall have an MTOM of less than 900 g, including payload.	EASA	jun-19	open	Regulation applicable								
UA Design and Airworthiness	EU 2019/945	Parts 1(6) and 2(10) UAS in class C0 and C1 shall be powered by electricity and have a nominal voltage not exceeding 24 V direct current (DC) or the equivalent alternating current (AC) voltage; its accessible parts shall not exceed 24 V DC or the equivalent AC voltage; internal voltages shall not exceed 24 V DC or the equivalent AC voltage unless it is ensured that the voltage and current combination generated does not lead to any risk or harmful electric shock even when the UAS is damaged.	EASA	jun-19	open	Regulation applicable								
UA Design and Airworthiness							WK58939 Evaluating Aerial Response Robot/Energy/Power; Endurance Range and Duration	A suite of standards test methods has been developed to measure maneuverability, endurance, communications, durability, logistics, autonomy, and safety to guide purchasing decisions, support operator training and measure proficiency.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018	
UA Design and Airworthiness	EU 2019/945	Parts 3(12) and 4(7) UAS in class C2 and C3 shall be powered by electricity and have a nominal voltage not exceeding 48 V DC or the equivalent AC voltage; its accessible parts shall not exceed 48 V DC or the equivalent AC voltage; internal voltages shall not exceed 48 V DC or the equivalent AC voltage unless it is ensured that the voltage and current combination generated does not lead to any risk or harmful electric shock even when the UAS is damaged.	EASA	jun-19	open	Regulation applicable								

UA Design and Airworthiness	EASA Decision	OSD#4 UAS developed to authority recognized design standards (e.g. industry standards)	EASA	oct-19	Specific	published												
UA Design and Airworthiness	EASA Decision	OSD#5 UAS is designed considering system safety and reliability	EASA	oct-19	Specific	published												
UA Design and Airworthiness	EASA Decision	OSD#10 Safe recovery from technical issue /	EASA	oct-19	Specific	published												
UA Design and Airworthiness	EASA Decision	OSD#12 The UAS is designed to manage the deterioration of external systems supporting UAS operation	EASA	oct-19	Specific	published												
UA Design and Airworthiness	EASA Decision	OSD#18 Automatic protection of the flight envelope from human errors	EASA	oct-19	Specific	published												
UA Design and Airworthiness	EASA Decision	OSD#19 Safe recovery from Human Error (Criterion #3 UAS design)	EASA	oct-19	Specific	published												
HMI	EASA Decision	OSD #20 - A Human Factors evaluation has been performed and the HMI found appropriate for the mission	EASA	oct-19	Specific	published												
HMI	Opinion 05-2019	Part 16(3) and 17(3) UAS Class C5 and C6 during flight shall provide the remote pilot with clear and concise information on the height of the UA above the surface or take-off point;	EASA	jun-20	Specific	Opinion published												
HMI	EU 2019/945	Part 1(4) and 2(4) UAS in class C0 and C1 shall be safely controllable with regards to stability, manoeuvrability and data link performance, by a remote pilot following the manufacturer's instructions, as necessary under all anticipated operating conditions including following the failure of one or, if appropriate, more systems	EASA	jun-19	open	Regulation applicable												Opinion 05-2019: to be safely controllable with regard to stability, manoeuvrability and the command and control link performance, by a remote pilot following the manufacturer's instructions
HMI	EU 2019/945	Part 6(2) UAS in class C4 shall be safely controllable and manoeuvrable by a remote pilot following the manufacturer's instructions, as necessary under all anticipated operating conditions including following the failure of one or, if appropriate, more systems;	EASA	jun-19	open	Regulation applicable												
HMI	EU 2019/945	Part 1(1) annex 1 UAS in class C2 and C3 shall be safely controllable with regards to stability, manoeuvrability and data link performance, by a remote pilot following the manufacturer's instructions, as necessary under all anticipated operating conditions including following the failure of one or, if appropriate, more systems;	EASA	jun-19	open	Regulation applicable												Opinion 05-2019: to be safely controllable with regard to stability, manoeuvrability and the command and control link performance, by a remote pilot with adequate
UA Design and Airworthiness	EASA Decision	OSD #21 - UAS designed and qualified for adverse environmental conditions (e.g. adequate sensors, DO-160 qualification)	EASA	oct-19	Specific	published												
UA Design and Airworthiness	EASA Decision	OSD#24 UAS designed and qualified for adverse environmental conditions (e.g. adequate sensors, DO-160 qualification)	EASA	oct-19	Specific	published												
UA Design and Airworthiness	EASA Decision	M#2 Effects of ground impact are reduced. A category. Measures, indicate the effect of the UAS impact dynamics (e.g. emergency parachute).	EASA	oct-19	Specific	published												
UA Design and Airworthiness	Opinion 05-2019	Part 16 A class C5 UAS may consist in a class C3 UAS fitted with an accessories kit that ensures the conversion of the UAS into a class C5 UAS. In this case, the class C5 label is affixed on the accessories kit. An accessories kit may only ensure conversion of a class C3 UAS that complies with (1) and provides the necessary interfaces to the accessories. The accessories kit shall not include changes to the software of the class C3 UAS. The accessories kit shall be designed, and each accessory shall be	EASA	jun-20	Specific	Opinion published												
UA Design and Airworthiness	EASA Decision	M#3 Technical containment in place and effective (e.g. tether)	EASA	oct-19	Specific	published												
							ASTM WK67357 New Specification for Light Unmanned Aircraft System Manufacturers Quality Assurance System	This specification establishes the minimum requirements for a quality assurance system for manufacturers of Light Unmanned Aircraft Systems or Light Unmanned Aircraft System kits, or both.	ASTM F38 Unmanned Aircraft Systems	Mar-19	specification	ongoing						
							ASTM WK 63407 Standard Specification for Required Product Information to be Provided with a Small Unmanned Aircraft System	This specification covers the minimum requirements for information that shall be provided by the sUAS OEM or seller of a new small unmanned aircraft, small unmanned aircraft kit, engines, propellers, or accessories (that is, radio, automated flight control system, remote pilot station, GPS, and so forth) as a part of the initial sale or transfer to the first end user. This specification does not apply to the sale or transfer of used small unmanned aircraft, engines, propellers, or accessories. This specification applies to small unmanned aircraft systems seeking civil aviation authority approval in the form of airworthiness certificates or other like documentation.	ASTM F38 Unmanned Aircraft Systems	oct-19	standard	ongoing	currently under ballot					
							F3478-20 Standard Practice for Development of a Durability and Reliability Flight Demonstration Program for Low-Risk Unmanned Aircraft Systems (UAS) under FAA Oversight	Demonstration plans developed in accordance with this practice will include all necessary content and key considerations to support an effective flight demonstration program aimed at approval or certification of UAS by the FAA through D&R demonstration.	ASTM F38 Unmanned Aircraft Systems		standard	published						

Qualified entities							ASTM WK62744 General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS)	Best practices to support professional entities receiving operator certification by a CAA, and provide practice for self- or third-party audit of operators of UAS.	ASTM F38 Unmanned Aircraft Systems	TBD	Best practice	ongoing	Draft
Manuals							ASTM F2968-16 Standard Specification for Aircraft Flight Manual (AFM) for a Small Unmanned Aircraft System (sUAS)	This specification provides the minimum requirements for an Aircraft Flight Manual (AFM) for an unmanned aircraft system (UAS) designed, manufactured, and operated in the small UAS (sUAS) category as defined by a Civil Aviation Authority (CAA). Depending on the size and complexity of the sUAS, an AFM may also contain the instruction for maintenance and continuing airworthiness for owner / operator authorized maintenance.	ASTM F38 Unmanned Aircraft Systems		standard	published	published
Automatic modes, takeoff, Landing, taxing							WK58931 Evaluating AerialResponse RobotManeuvering: Maintain Position and Orientation	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately maintain position and orientation (pose) in open space relative to an object of interest. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission. The system includes a remote operator in control of all functionality and any assistive features or autonomous behaviors that improve the effectiveness or efficiency of the overall system. This test method may be performed anywhere the specified apparatuses and environmental conditions can be implemented as described. Results should be considered within the context of related test methods in the Maneuvering suite when comprehensively evaluating robotic system capabilities.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Automatic modes, takeoff, Landing, taxing							WK58932 Evaluating AerialResponse RobotManeuvering: Orbit a Point	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately orbit an object of interest. Results should be considered within the context of related test methods in the Maneuvering suite when comprehensively evaluating robotic system capabilities. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission. The system includes a remote operator in control of all functionality and any assistive features or autonomous behaviors that improve the effectiveness or efficiency of the overall system. This test method may be performed anywhere the specified apparatuses and environmental conditions can be implemented as described.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	
Detect and avoid							WK58933 Evaluating AerialResponse RobotManeuvering: Avoid Static Obstacles	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to avoid static obstacles.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Detect and avoid							WK58934 Evaluating AerialResponse RobotManeuvering: Pass Through Openings	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to pass through openings of various sizes and orientations.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Automatic modes, takeoff, Landing, taxing							WK58935 Evaluating AerialResponse RobotManeuvering: Land Accurately (Vertical)	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately land vertically within a defined area.	ASTM E54 Homeland Security Applications	TBD	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
UAS-ATM							Specifications for the Use of Military Unmanned Aerial Vehicles (UAV) as Operational Air Traffic (OAT) outside segregated airspace specification, v 1.0, 2007	This specification addresses aspects of military UAV ATM, dealing briefly with extant regulations that impact upon the UAV specifications and then explaining the nature of UAV airspace requirements. It also summarises a number of national UAV ATM regulations, albeit none were suitable for adoption into EUROCONTROL specifications	EUROCONTROL		specification	published	
UAS-ATM							Air Traffic Management Guidelines for Global Hawk in European Airspace, v 1.0, 2010	These Guidelines establish a set of minimum ATM requirements for Global Hawk (GH) / Euro Hawk (EH) flight in European airspace, with the primary purpose of enabling GH/EH operators to use them as the basis for negotiating access to national airspace within Europe. The Guidelines envisage the isolation of GH/EH from other airspace users by requiring it to climb-out and recover in segregated airspace and to fly IFR/OAT in the cruise in non-segregated airspace at high altitudes that are above those occupied by manned aviation.	EUROCONTROL		guidance material	published	
Local E-identification							prEN4709-2 Aerospace series - Unmanned Aircraft Systems (UAS) - Security Requirements	This European standard will provide means of compliance to cover Part 6 and the relevant requirements from part 2 to 4 of the delegated act. DIRECT REMOTE IDENTIFICATION shall comply with the following: Ensure, in real time during the whole duration of the flight of the UA to which it is attached, the direct periodic broadcast, using an open and documented transmission protocol, of the following data in a way that they can be received directly by existing mobile devices within the broadcasting range : (a) the UAS operator registration number; (b) the physical serial number of the add-on compliant with standard ANSICTA-2063; (c) the geographical position of the UA, its height above the take-off point and associated date and time; (d) the direction and speed of the UA; and (e) the geographical position of the UA pilot (or if not available (class 1), the take-off point.	ASD-STAN D5WG8	sept-21	preEN / European standard	ongoing	
Standard scenarios							ASTM F3196-16 Standard Practice for Seeking Approval for Extended Visual Line of Sight (EVLLOS) or Beyond Visual Line of Sight (BVLOS) Small Unmanned Aircraft System (sUAS) Operations	Compliance with this practice is recommended as one means of seeking approval from a civil aviation authority (CAA) to operate a small unmanned aircraft system (sUAS) to fly extended visual line of sight (EVLLOS) or beyond visual line of sight (BVLOS), or both. Any regulatory application of this practice to sUAS and other unmanned aircraft systems (UASs) is at the discretion of the appropriate CAA.	ASTM F38 Unmanned Aircraft Systems		standard	published	Body of standard revised and published incorporating Outfinder results, appendix is pending. To be revised and amended to include use case scenarios: package delivery, infrastructure inspection, linear inspection, search and rescue, emergency response, terminal operations, agriculture. First of these expenditures (package delivery) to be completed Jun 2018. Final available but revisions to standard will be incorporated in Jan 2018 after Pathfinder Technical Interchange.
Standard scenarios							ASTM WK 62344 BVLOS Package Delivery as an Appendix to F3196-17	Appendix to to ASTM F3196-17. The main purpose of this revision is to add an Appendix that can be used in developing proposed mitigation strategies for package delivery sUAS BVLOS operations	ASTM F38 Unmanned Aircraft Systems	jun-19	standard	ongoing	Working group formed and continues
Operations							ASTM F2948-10 Standard Practice for Handling of Unmanned Aircraft Systems at Divert Airfields		ASTM F38 Unmanned Aircraft Systems		practice	published	

Operations								ISO 21384-3 - Requirements for safe civil RPAS/UAS operations and applies to all types, categories, classes, sizes and modes of operation of UAS	Requirements for safe commercial UAS operations and applies to all types, categories, classes, sizes and modes of operation of UAS.	ISO	déc-18	standard	published	
UAS-ATM								ARP#### Access to controlled airspace		SAE G-30 UAS Operator Qualifications Committee	mai-19	recommended practice	planned	
Standard scenarios								ARP#### Flight beyond visual line of sight		SAE G-30 UAS Operator Qualifications Committee	mai-19	recommended practice	planned	
Standard scenarios								ARP#### Night operations		SAE G-30 UAS Operator Qualifications Committee	mai-19	recommended practice	planned	
Standard scenarios								ARP#### Aerial photography		SAE G-30 UAS Operator Qualifications Committee	juin-19	recommended practice	planned	
Standard scenarios								ARP#### Power line inspection		SAE G-30 UAS Operator Qualifications Committee	juil-19	recommended practice	planned	
Standard scenarios								ARP#### Precision agriculture		SAE G-30 UAS Operator Qualifications Committee	août-19	recommended practice	planned	
Standard scenarios								ARP#### Bridge inspection		SAE G-30 UAS Operator Qualifications Committee	sept-19	recommended practice	planned	
Standard scenarios								ARP#### Train right-of-way's		SAE G-30 UAS Operator Qualifications Committee	oct-19	recommended practice	planned	
Standard scenarios								ARP#### Flare stack inspections		SAE G-30 UAS Operator Qualifications Committee	nov-19	recommended practice	planned	
Standard scenarios								WK58243 New Guide for Visual Inspection of Building Façade using Drone	This standard consists of guidelines for utilizing drones with cameras to document facade conditions with video and still photography. The purpose of this standard is to establish procedures and methodologies for conducting visual inspections of building facades via drone, and documenting such inspections.	ASTM E06 Performance of Buildings	janv-18	guide	ongoing	
Navigation								WK58677 Evaluating AerialResponse RobotSensing: Visual Image Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the visual (electro-optical) image acuity of the system as viewed through a control station. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission. The system includes a remote operator in control of all functionality and any assistive features or autonomous behaviors that improve the effectiveness or efficiency of the overall system. This test method may be performed anywhere the specified apparatuses and environmental conditions can be implemented as described. Results should be considered within the context of related test methods in the Maneuvering suite when comprehensively evaluating robotic system capabilities.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Ground control station								WK58925 Evaluating AerialResponse RobotSensing: Visual Color Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the visual (electro-optical) color acuity of the system as viewed through a control station.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Ground control station								WK58926 Evaluating AerialResponse RobotSensing: Visual Dynamic Range	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the visual (electro-optical) dynamic range of the system as viewed through a control station.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
C3 datalink and communication								WK58927 Evaluating AerialResponse RobotSensing: Audio Speech Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the audio speech acuity of the system as heard bi-directionally between a control station and aerial robot in flight.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Ground control station								WK58928 Evaluating AerialResponse RobotSensing: Thermal Image Acuity	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the thermal image acuity of the system as viewed through a control station. This test method applies to aerial systems operated remotely from a standoff distance appropriate for the intended mission.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Ground control station								WK58929 Evaluating AerialResponse RobotSensing: Thermal Dynamic Range	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the thermal dynamic range of the system as viewed through a control station.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Ground control station								WK58930 Evaluating AerialResponse RobotSensing: Latency of Video, Audio, and Control	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the latency of video, audio, and control sub-systems as viewed through a control station.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Detect and avoid								WK58936 Evaluating AerialResponse RobotSituational Awareness: Identify Objects (Point and Zoom Cameras)	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to identify objects of interest in the environment using cameras (electro-optical and thermal) from defined altitudes in open space.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Standard scenarios								WK58937 Evaluating AerialResponse RobotSituational Awareness: Inspect Static Objects	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to inspect objects of interest in close proximity.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18
Standard scenarios								WK58938 Evaluating AerialResponse RobotSituational Awareness: Map Wide Areas (Stitched Images)	The purpose of this test method is to specify the apparatuses, procedures, and performance metrics necessary to quantitatively evaluate the system capability to accurately map wide areas with objects of interest in the environment.	ASTM E54 Homeland Security Applications	avr-18	standard	ongoing	E54 Full Committee adjudication February 26 to March 2, 2018. Delayed till Apr-18

	Standard scenarios							ASTM WK52858 Small Unmanned Aircraft Systems (sUAS) for Land Search and Rescue	This classification defines small unmanned aircraft system (sUAS) land search and rescue resources in terms of their capabilities. It provides a means by which resource managers and sUAS pilots/operators can convey to emergency management the tasks for which their systems are capable of performing.	ASTM F32 Search and Rescue	TBD	standard	ongoing	
	Standard scenarios							ASTM WK54226 sUAS Operations in Search and Rescue Operations	This guide establishes a framework within which sUAS search and rescue (SAR) operations shall be conducted as part of the National Incident Management System (NIMS)/Incident Command System (ICS). 1.2 The requirements of this guide shall apply to individuals, agencies, and organizations that respond to SAR operations, including those not regulated by government mandates.	ASTM F32 Search and Rescue	TBD	standard	ongoing	
	Standard scenarios							ASTM WK65042 New Specification for Operation over People	Recent research conducted on risk, safety, design, operations and impact to inform development of standard with supporting documentation from Pathfinder studies. Using results of the Pathfinder Program, impact testing and mitigations such as deployable sUAS parachutes to be incorporated into standard.	ASTM F38 Unmanned Aircraft Systems	mar-19	specification	ongoing	Final draft for ballot in October 2018, adjudicating comments
	UA Design and Airworthiness							ASTM F3389-20 Test Methods for Assessing the Safety of Small Unmanned Aircraft System Impacts	Develop a draft standard for product marking of UAS weighing 250 grams or less. Develop draft standard for Category 2, 3, and 4 UAS that: (1) Establishes a test method(s) to measure typical or likely impact energy of the small unmanned aircraft when the aircraft is operating in the most probable failure mode(s) to determine whether it meets the FAA specified impact energy threshold. Testing may be subject to manufacturer defined operating limitations, if any. The impact energy threshold used in the standards may account for the energy dissipation caused by the physical design of the small unmanned aircraft and likely impact scenarios.	ASTM F38 Unmanned Aircraft Systems		standard	published	
	Risk Assessment							ASTM F3178-16 Standard Practice for Operational Risk Assessment of Small Unmanned Aircraft Systems (sUAS)	Preparation of an ORA in accordance with this practice is intended to reduce the risk of an operation in which system complexity is minimal, the risk is conducted in a lower risk environment, and the likelihood for harm to people or property, though present, is reduced to an acceptable level. As mission complexity increases, the operational environment may become less risk tolerant.	ASTM F38 Unmanned Aircraft Systems		standard	published	This will be reference in AC for Special Class §21.17(b)
	Manuals							ASTM WK60938 New Practice for General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS)	This standard defines the requirements for General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS). The standard addresses the requirements and/or best practices for documentation and organization of a professional operator (i.e., for compensation and hire).	ASTM F38 Unmanned Aircraft Systems	sept-18	specification	ongoing	Draft Complete - will be balloted Jun 2018
M	Take off/ Landing zones							F3423/F3423M-22 Standard Specification for Vertipod Design	To support the design of civil vertipods and vertistops for the landing and takeoff of VTOL aircraft boarding and discharging passengers or cargo. The profession of electric-powered VTOL should be carefully considered in the development of this document. The standard must be scalable to address aircraft ranging in size and kinetic energy, including unmanned and optionally piloted aircraft.	ASTM F38.02	Jul-22	specification	published	
	UAS-ATM							STANAG 7234 Remotely Piloted Aircraft Systems (RPAS) Airspace Integration (AI) AATMP-51		NATO FINAS	2018	standard	ongoing	Under development
	C3 datalink and communication							STANAG 7232 Unmanned Aerial Systems: Tactics Techniques and Procedures - ATP-3.3.8.2 Edition A	Provide standardized tactics, techniques, and procedures 217 for the planning, command and control (C2), and employment of unmanned aircraft systems 218 (UAS) in NATO operations	NATO MCASB/JCGUAS OS	2018	standard		
								WK62744 General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS)	This standard defines the requirements for General Operations Manual for Professional Operator of Light Unmanned Aircraft Systems (UAS). The standard addresses the requirements and/or best practices for documentation and organization of a professional operator (i.e., for compensation and hire). The intent is for this standard to support professional entities that will receive operator certification by a CAA, and provide standards of practice for self- or third-party audit of operators of UAS Not all CAAs have operator certificates. This would provide a standard for operators and identify gaps that are not currently addressed as it relates to: (1)Individuals, who are currently remote pilots (i.e. FAA under Part 107) in jurisdictions that do not separately certify Operators, who want to voluntarily comply with a higher standard, and (2)Operators, who are seeking certification from a CAA for Light Unmanned Aircraft Systems, who want to voluntarily comply with an industry standard (3)Public agencies interested in developing unmanned aircraft systems programs.	ASTM F38 Unmanned Aircraft Systems	Mar-19	standard	ongoing	Under development
								WK69336 Framework for Using ASTM Standards for UAS	This guide provides some major themes and examples for consideration related to compliance which are not necessarily captured in any single standard pertinent to UAS. The outline of this document is intended to loosely reflect the process that an organization would go through in order to reach and maintain production of UAS that is demonstrably compliant with the applicable Consensus-based standards. The guide describes the current standards and identifies gap areas to support unmanned aircraft operations for commercial purposes. A CAA may, at their discretion, use this guide to aid the development of regulations. A commercial operator may, at their discretion, use this guide to aid their applications for regulatory approval; for example, when submitting a safety case as part of a Specific Operations Risk Assessment (SORA)	ASTM F38 Unmanned Aircraft Systems	Mar-19	guide	ongoing	
								prEN4709-4 Aerospace series - Unmanned Aircraft Systems (UAS) - Security requirements	This European standard will provide means of compliance to cover lighting related requirements for part 2 to 4 of the delegated act. The purpose is to be able to verify that an UA is equipped with lights which: -ensure controllability of the UA -ensure conspicuity of the aircraft at night, the design of the light shall allow a person on the ground to distinguish a UA from a manned aircraft The standards will address: -Definition of types, technical requirements and technical parameters of UA lights (e.g. position of lights for different UA categories, intensity for different operation modes) -Definition of purpose, test procedures, requirements and compliance rules to evaluate UA lights	ASD-STAN D5WG8	sept-21	preEN / European standard	ongoing	
								ISO/NP 5015-1	Operational procedures for passenger-carrying UAS	ISO/TC 20/SC 16/WG 3	nov-21	standard	ongoing	
								ISO/NP 5015-2	Operation of vertipods for unmanned aircraft (UA)	ISO/TC 20/SC 16/WG 3	nov-20	standard	ongoing	
								ISO/WD 24354	Payload interface for Small, Civil UAS	ISO/TC 20/SC 16	TBD	standard	ongoing	
								ISO/WD 24355	Flight control system for Small Multicopter UAS	ISO/TC 20/SC 16	TBD	standard	ongoing	

										ASTM WK75223 New Specification for Positioning Assurance, Navigation, and Time Synchronization for Unmanned Aircraft Systems	The Standard Specification must define Positioning Assurance and define minimum requirements for the UAS to know where it is positioned (and potentially localized) and the error associated with that position. The Standard Specification must also define Navigation and define minimum requirements for UAS navigation. The Standard Specification must define Time Synchronization and define minimum requirements for the UAS to know that the time value that its systems are using is assured and trusted. While none of these essential functions are completely unique to BLOS operations, from a safety standpoint they become more critical for BVLOS/BLOS operations.	ASTM F38.02	Summer 2022	standard	ongoing	Title and description were changed in v7.0 based on a change proposal from ASTM
8	FCL															
Remote pilot competence	EU 2019/947	UAS.OPEN.20(4) be performed by a remote pilot: (a) familiarised with the user's manual provided by the manufacturer of the UAS; (b) in the case of an unmanned aircraft class C1, as defined in Part 2 of the Annex to Delegated Regulation (EU) [2019]0306-021, who has completed an online training course followed by completing successfully an online theoretical knowledge examination provided by the competent authority or by an entity recognised by the competent authority of the Member State of registration of the UAS operator. The examination shall comprise 40 multiple-choice questions distributed appropriately across the following subjects: i. air safety; ii. airspace restrictions; iii. aviation regulation; iv. human performance limitations; v. operational procedures; vi. UAS general knowledge; vii. privacy and data protection; viii. insurance; ix. security.	EASA	jun-19	open and specific	Regulation applicable from 1 July 2020										
										ISO 23665 - Unmanned aircraft systems -- Training for personnel involved in UAS operations	The purpose of this international standard is that the persons who work for UAS operation receive appropriate education and obtain required knowledge and skill. Persons or educational organizations qualified according to this standard will be internationally regarded. It will enhance international operation of UAS, personal exchange and international trade.	ISO/TC 20/SC 16/WG 3	oct-20	Standard	published	
Remote pilot competence										ARP5707 - Pilot Training Recommendations for Unmanned Aircraft Systems (UAS) Civil Operations	This document provides an approach to the development of training topics for pilots of Unmanned Aircraft Systems (UAS) for use by operators, manufacturers, and regulators. The identification of training topics is based initially on Practical Test Standard (PTS) topics for manned aircraft pilots. The topics identified could be used for the construction of a PTS for UAS commercial pilot operations and a PTS for a UAS pilot instrument rating. The UAS commercial pilot rating would contain restrictions on the types of operations that could be flown that would be dependent on the type of UAS used. The UAS type would also influence the specific training topics that would be covered. This document is not intended to outline the requirements for other crewmembers, such as observers, payload operators, or ground personnel, nor does it distinguish between different levels of pilot authority or discuss the roles for pilot-in-command, supplemental pilot, or observer.	SAE G-30 UAS Operator Qualifications Committee & G-10U Unmanned Aerospace Vehicle Committee		recommended practice	published	
Remote pilot competence										ARP#### Common operator qualifications		SAE G-30 UAS Operator Qualifications Committee	mai-19	recommended practice	planned	
Remote pilot competence	EU 2019/947	UAS.OPEN.030(2) be performed by a remote pilot who is familiar with the user's manual provided by the manufacturer of the UAS and holds a certificate of remote pilot competency issued by the competent authority or by an entity recognised by the competent authority of the Member State of registration of the UAS operator. This certificate shall be obtained after complying with all of the following conditions and in the order indicated: (a) completing an online training course and passed the online theoretical knowledge examination as referred to in point (4)(b) of point UAS.OPEN.020; (b) completing a self-practical training in the operating conditions of the subcategory A3 set out in points (1) and (2) of point UAS.OPEN.040; (c) declaring the completion of the self-practical training defined in point (b) and passing an additional theoretical knowledge examination provided by the competent authority or by an entity recognised by the competent authority of the Member State of registration of the UAS operator. The examination shall comprise at least 30 multiple-choice questions aimed at assessing the remote pilot's knowledge of the technical and operational mitigations for ground risk, distributed appropriately across the following subjects: i. meteorology; ii. UAS flight performance; iii. technical and operational mitigations for ground risk.	EASA	jun-19	open and specific	Regulation applicable from 1 July 2020										
maintenance										ASTM WK76061 New Guide for Lightweight UAS Maintenance Technician Qualification	The purpose of this guide is to address the basic fundamental subject knowledge, task performance, and task knowledge activities and functions for UAS maintenance professionals to be titled UAS Maintenance Technicians	ASTM F38 Unmanned Aircraft Systems and F46 Aerospace Personnel	jun-18	standard	ongoing	Undergoing revisions prior to ballot
Remote pilot competence										F3379-20 Guide for Training Public Safety Remote of Unmanned Aircraft Systems Endorsement	To develop a standard that defines the requirements for Training for Public Safety Remote Pilot of Unmanned Aircraft Systems (UAS) Endorsement. The guide describes the knowledge, skills, and abilities required to operate unmanned aircraft for public safety purposes. A CAA may, at their discretion, use this guide to aid the development of regulations. An approved ASTM guide that describes required education, training, and continuing professional development for those performing as professional public safety remote pilot.	ASTM F38 Unmanned Aircraft Systems		standard	published	
Remote pilot competence										ASTM F3266 Standard Guide for Training for Remote Pilot in Command of Unmanned Aircraft Systems (UAS) Endorsement	Establish criteria for Training and Certification of sUAS Pilots, Instructors, and School Houses. This practice defines the knowledge, skills, and abilities sUAS pilots require for the conduct training and flight operations for Small Unmanned Aircraft Systems (sUAS) in the NAS. The Training and Certification of sUAS Pilots, Instructors, and School Houses include areas to cover pilot qualifications, training and proficiency, instructor certification, and sUAS flight training facility operations. This document sets forth standards to meet the requirements to establish quality training and certification programs, and facilitate aviation safety.	ASTM F38 Unmanned Aircraft Systems	avr-18	standard	published	

	Noise&Environment	EU 2019/945	Part 4(6) UAS in class C3 shall have, unless it is a fixed-wing UA, the indication of the guaranteed A-weighted sound power level LWA determined as per Part 13 affixed on the UA and/or its packaging as per Part 14.	EASA	Jul-19	open	Regulation applicable							
11	SC Light-UAS													
								EUROCAE Document	ED-80 Design Assurance Guidance for Airborne Electronic Hardware	EUROCAE	av-00	standard	published	Added to RDP as standard was recommended by AW-Drones
								EUROCAE Document	ED-12C Software Considerations in Airborne Systems and Equipment Certification	EUROCAE	Issued in January 2012 (incl. Corrigendum 1 released in February 2021)	standard	published	Added to RDP as standard was recommended by AW-Drones
								ASTM F44	ASTM F3367-21 Simplified High Intensity Radiated Field (HIRF) Protection in Level 1 and Level 2 Aircraft	ASTM	May-2021	standard	published	Added to RDP as standard was recommended by AW-Drones
								ASTM F44	ASTM F3309 - Standard Practice for Simplified Safety Assessment of Systems and Equipment in Small Aircraft	ASTM	published	standard	published	Added to RDP as standard was recommended by AW-Drones
								IEC TC 21/SC 21A - Secondary cells and batteries containing alkaline or other non-acid electrolytes	IEC 62133-2017 Secondary cells and batteries containing alkaline or other non-acid electrolytes - Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications	IEC	Jul-21	standard	published	Added to RDP as standard was recommended by AW-Drones